



TECHNICAL DATA / FEATURES

- dimensions: 100x100x76
- luminous flux of the LED module: 800 lm
- luminous flux of the lamp: 500 lm
- maximum power: 11W
- nominal voltage: 12V-24V DC
- permissible power supply voltage: 10.5V-30V DC
- source of light: 3 x LED
- colour temperature: 5000-7000K
- light distribution angle: 40° x 22°
- IP rating: IP67, IP69K, IP66
- work temperature: -40°C - +80°C
- housing's material: aluminium/plastic
- lens' material: plastic
- built-in connectors: AMP Faston 250, Deutsch DT, AMP SuperSeal 1.5
- other: protection:
 - against overheating
 - against reverse polarisation



ADDITIONAL INFORMATION

Work lamps are used to illuminate working space near vehicles, tractors, slow-moving machines and any other places where indicated voltage is available.

The lamps comply with EMC Directive 2004/108/EC. They do not emit electromagnetic interference as well as they are resistant to it's influence.

Correct polarity required.

Mounting: as a freestanding on body panels. They can be installed in any position (standing, hanging, on side).

LED3 lamps are available with reversing approval (AR).

It is possible to install needed connectors for a version with cable (on request).




Useful parts while installing:

- deutsch plug DT06-2S 2-pin - cat. No. A.07135
- AMP SuperSeal 1,5 plug 2-pin - cat. No. A.07137
- AMP Faston 250 plug 2-pin - cat. No. A.07138

Replacement parts:

- brackets - cat. No. CAR2.41910
- neodymium magnet $\phi 89/500N$ (1 pc.) - cat. No. CAR4.51320

DIMENSIONS



Cat. number	IP rating			Accessories				Mounting method				Connectors											
	IP66	IP67	IP69K	handle	cable 0.5 m	cable 1.9 m	cable 8 m	switch	cigarette lighter plug	installed vertically up	suspended	side	any	rear	Bracket	M8	omega	CAR2	neodymium magn.	AMP Faston 250	Deutsch DT	AMP SuperSeal 1,5	
LED3.47700		✓	✓						✓	✓	✓	✓											
LED3.47780		✓	✓		✓			✓		✓	✓	✓											
LED3.47706	✓		✓							✓	✓	✓								✓			
LED3.47707		✓	✓							✓	✓	✓											
LED3.47711		✓	✓							✓	✓	✓										✓	
LED3.47720		✓	✓		✓					✓	✓	✓											
LED3.47782		✓	✓		✓			✓		✓	✓	✓											
LED3.47726	✓		✓							✓	✓	✓							✓				
LED3.47727		✓	✓							✓	✓	✓											
LED3.47728		✓	✓							✓	✓	✓											
LED3.47710		✓	✓		✓					✓	✓	✓											
LED3.47781		✓	✓		✓			✓		✓	✓	✓											
LED3.47716	✓		✓		✓					✓	✓	✓								✓			

Cat. number	IP rating			Accessories				Mounting method				Connectors											
	IP66	IP67	IP69K	handle	cable 0.5 m	cable 1.9 m	cable 8 m	switch	cigarette lighter plug	installed vertically up	suspended	side	any	rear	Bracket	M8	omega	CAR2	neodymium magn.	AMP Faston 250	Deutsch DT	AMP SuperSeal 1,5	
LED3.47717		✓	✓							✓	✓	✓											
LED3.47718		✓	✓							✓	✓	✓											
LED3.47730		✓	✓		✓					✓	✓	✓											
LED3.47783		✓	✓		✓					✓	✓	✓											
LED3.47736		✓	✓					✓		✓	✓	✓											
LED3.47737		✓	✓							✓	✓	✓											
LED3.47738		✓	✓							✓	✓	✓											
LED3.47739		✓	✓							✓	✓	✓											
LED3.47795		✓	✓					✓		✓	✓	✓											
LED3.47798		✓	✓							✓	✓	✓											
LED3.47796		✓	✓							✓	✓	✓											
LED3.47739		✓	✓							✓	✓	✓											
LED3.47704		✓	✓							✓	✓	✓											
LED3.47705		✓	✓							✓	✓	✓											